## MIL-E-QUAL® ELECTRICAL CURRENT RATING CHART

CONTACT SIZE	CONDUCTOR SIZE - AWG	NUMBER OF CONDUCTORS	CURRENT RATING
	#12	1 through 3	23.0A
		4 through 6	17.0A
		7 through 9	13.0A
	#14   1 through 3     #14   4 through 6     7 through 9   1 through 3     #16   4 through 6     7 through 9   1 through 3     #16   7 through 9	1 through 3	17.0A
#12		4 through 6	12.75A
		11.0A	
		1 through 3	13.0A
		4 through 6	9.75A
		7 through 9	8.45A
	#16 1 through 3   #16 7 through 10   10 through 20 21 through 30   21 through 30 31 and up   #18 1 through 6   7 through 9 10 through 20   21 through 30 31 and up   #18 10 through 20   21 through 30 31 and up	1 through 3	13.0A
		4 through 6	9.75A
		7 through 10	8.45A
		10 through 20	5.85A
		21 through 30	4.55A
		31 and up	3.9A
		10.0A	
1110		7.5A	
#16	#10	7 through 9	6.5A
	#18	10 through 20	4.5A
		21 through 30	3.5A
		31 and up	3.0A
	#20	1 through 3	7.5A
		4 through 6	5.6A
		7 through 9	4.8A
		10 through 20	3.4A
		21 through 30	2.62A
		31 and up	2.3A

## TOOLING

## MIL-E-QUAL® MANUAL CONTACT CRIMPING TOOL

Handle	Description	Positioner	Contact Sizes	Wire Sizes	Conductor Strip Length
	Hand Crimp Tool		#12	12-14 AWG	7/32 in
359-24		358-112	#16	16-18-20 AWG	9/32 in

## **MIL-E-QUAL® MANUAL CONTACT INSERTION TOOL**

Handle	Description	Insertion Bits	Contact Sizes
356-1	Single Contact Hand Tool	356-12	#12
		356-16	#16