


TWIST-LOCK HPC SERIES SPEAKON® STYLE CONNECTORS



5555 N ELSTON AVE | CHICAGO, IL | P: 773.792.2700 | F: 773.792.2129 | WWW.SWITCHCRAFT.COM



Switchcraft's HPC connectors are fully compatible with Speakon® connectors from all major manufacturers

HPCC4FT CONNECTORS

Switchcraft's new 4 pole speaker and power connector builds on the existing HPC series and adds a new twist-lock option. This new option has the same industry leading specifications as Switchcraft's HPCC4F cable plug and the same built-to-last quality customers have come to expect from Switchcraft for over 70 years.

MARKETS

- Loudspeakers
- AC Power Transmission
- Audio Amplifiers
- Medical Devices
- Process Controls

SPECIFICATIONS

- Part Number: HPCC4FT
- Number of Contacts: 4
- Current: **30A** per UL 1977
- Voltage: 1,500V AC per Mil-Std 202, Method 301
- Insulation Resistance: > 2T Ohms
- Contact Resistance: 1m Ohm
- Touch Proof: per IEC 65 and 1010-1
- Life: 1,000 Insertion/Withdrawal Cycles
- Temperature Limits: -55°C to 85°C
- Seal Rating (mated): IP25, IEC 529

TEST CRITERIA

- Salt Spray: Mil-Std 202, Method 101D, Cond B
- Thermal Shock: Mil-Std 202, Method 107G
- Moisture Resistance: Mil-Std 202, Method 107G
- Ambient Temperature Life: Mil-Std 202, Method 108A
- Shock: Mil-Std 202, Method 213B, Cond. K
- Vibration: Mil-Std 202, Method 201A